


# Internal HDD Cage

## BPU-126-SA

1 x 5.25" to 6 x 2.5" SATA Hot-Swap Backplane Cage



### Introduction

High level RAID and high availability storage in compact design, the BPU-126-SA adds extra storage and hot-swap capability to satisfy any application needs. The BPU-126-SA is constructed of light weight and durable aluminum material with two cooling fans to ensure best heat dissipation required for high performance 2.5" laptop SATA drives. It is designed with excellent front to back vent airflow. Hard drives can also be removed or added to the system without turning off your system power or restarting your computer. The BPU-126-SA is an ideal solution for RAID and JBOD applications.

### Features

- All Aluminum Material Solid Construction for Best Heat Dissipation
- Support 6 x 2.5" SATA I/II HDDs
- Support HDD Thickness 9.5mm
- High Performance Transfer Rate Up to 3 Gb/s
- Plug & Play, Hot Swappable
- Built-in 2 x 40mm Cooling Fans
- LED for Power

### Specifications

Hot Swap	6x2.5"HDD
Standard Drive Bays	5.25" Drive: 1
Dimension (W x H x D)	146 x 42 x 178 mm
Material	Aluminum Body
Indicators	LED for Power
HDD Interface	2.5" HDD SATA
Weight	1.6 lbs
Connectors	Standard 4-pin Molex and 7-pin Data

## BPU-124V2-SS

1 x 5.25" to 4 x 2.5" SATA/SAS 6.0 Gb/s Hot-Swap Backplane Cage



### Introduction

High level Raid and high availability storage in compact design, the BPU-124V2-SS adds extra storage and hot-swap capability to satisfy any application needs. The BPU-124V2-SS is constructed of light weight and durable aluminum material with two cooling fans to ensure best heat dissipation required for high performance 2.5" laptop SAS/SATA drives. It is designed with excellent front to back vent airflow. Hard drives can also be removed or added to the system without turning off your system power or restarting your computer. The BPU-124V2-SS is an ideal solution for RAID and JBOD applications.

### Features

- All Aluminum Material Solid Construction for Best Heat Dissipation
- LED for Power & HDD Activity
- Built-in 2 x 40mm Cooling Fans
- Plug & Play, Hot Swappable
- Support HDD Thickness from 9.5 to 15mm
- High Performance Transfer Rate up to 6.0 Gb/s
- Support 4 x 2.5" SAS I/II (Dual Channel) & SATA I/II/III HDDs

### Specifications

Hot Swap	4x2.5"HDD
Cooling Fan [optional]	2x40mm
Standard Drive Bays	5.25" Drive: 1
Dimension (W x H x D)	146 x 42 x 173 mm
Material	Aluminum Body
Indicators	Power On: solid blue HDD Access: blue blinking
HDD Interface	2.5" SATA I/II/III, SAS I/II
Weight	1.8 lbs
Connectors	Standard 15-pin Power and 7-pin Data